

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGE5003                |
| 光源       | LLD2000NCE1 ×1 531.0 lm |
| 管理番号     | K0181587 ( 0 ) DR 1     |
| BZ分類     | BZ5                     |

| 器具効率           |                    | 83 %<br><br>上方光束<br>12 %<br>下方光束<br>71 % | 反射率  | 天井  | 80 % |      |                   |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|----------------|--------------------|------------------------------------------|------|-----|------|------|-------------------|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|                |                    |                                          |      | 壁   | 70   | 50   | 30                | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|                |                    |                                          |      |     | 床    | 10 % |                   |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|                |                    |                                          |      |     |      | 室指数  | 照明率 ( X0.01 ) ZCM |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率            |                    | 良<br>中<br>否                              | 0.63 | 0.6 | 44   | 34   | 27                | 23 | 42   | 33   | 27 | 22 | 39   | 31   | 26 | 22 | 36   | 29   | 24 | 21 | 18  |     |
|                |                    |                                          | 0.6  | 0.8 | 52   | 42   | 36                | 31 | 50   | 41   | 35 | 30 | 46   | 39   | 33 | 29 | 43   | 36   | 32 | 28 | 25  |     |
|                |                    |                                          | 0.56 | 1.0 | 57   | 48   | 42                | 37 | 55   | 47   | 41 | 36 | 51   | 44   | 39 | 35 | 47   | 41   | 37 | 33 | 30  |     |
|                |                    |                                          | 1.25 | 62  | 54   | 48   | 43                | 60 | 52   | 46   | 42 | 56 | 49   | 44   | 40 | 52 | 46   | 42   | 39 | 35 |     |     |
| 下方投影面積         |                    | cm <sup>2</sup>                          | 1.5  | 66  | 58   | 52   | 47                | 63 | 56   | 51   | 46 | 59 | 53   | 48   | 44 | 55 | 50   | 46   | 43 | 39 |     |     |
|                |                    |                                          | 2.0  | 70  | 64   | 58   | 54                | 68 | 62   | 57   | 53 | 63 | 58   | 54   | 51 | 59 | 55   | 51   | 48 | 44 |     |     |
| 等価発光面積         | cm <sup>2</sup>    | 2.5                                      | 73   | 68  | 63   | 59   | 71                | 66 | 61   | 58   | 66 | 62 | 58   | 55   | 62 | 58 | 55   | 53   | 48 |    |     |     |
|                |                    | 3.0                                      | 75   | 70  | 66   | 62   | 73                | 68 | 64   | 61   | 68 | 64 | 61   | 58   | 64 | 61 | 58   | 56   | 51 |    |     |     |
| H <sub>m</sub> | 1.30H <sub>m</sub> | 1.30H <sub>m</sub>                       | 4.0  | 78  | 74   | 70   | 67                | 76 | 72   | 69   | 66 | 71 | 68   | 65   | 63 | 66 | 64   | 62   | 60 | 55 |     |     |
|                |                    |                                          | 5.0  | 80  | 76   | 73   | 70                | 77 | 74   | 71   | 69 | 73 | 70   | 68   | 66 | 68 | 66   | 64   | 62 | 57 |     |     |
|                |                    |                                          | 7.0  | 82  | 79   | 77   | 74                | 79 | 77   | 75   | 73 | 75 | 73   | 71   | 69 | 70 | 69   | 67   | 66 | 60 |     |     |
|                |                    |                                          | 10.0 | 83  | 81   | 79   | 78                | 81 | 79   | 77   | 76 | 76 | 75   | 73   | 72 | 72 | 71   | 69   | 68 | 63 |     |     |

