

屋内照明器具特性	
品番 (品名)	XLGE5008
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0181590 (0) DR 1
BZ分類	BZ5

器具効率		8 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 2 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		7 1 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 4	3 4	2 7	2 3	4 2	3 3	2 7	2 3	3 9	3 1	2 6	2 2	3 6	2 9	2 5	2 1	1 9	
			0 . 6	0 . 8	5 2	4 2	3 6	3 1	5 0	4 1	3 5	3 0	4 6	3 9	3 3	2 9	4 3	3 7	3 2	2 8	2 5	
			0 . 5 6	1 . 0	5 7	4 8	4 2	3 7	5 5	4 7	4 1	3 6	5 1	4 4	3 9	3 5	4 8	4 2	3 7	3 3	3 0	
				1 . 2 5	6 2	5 4	4 8	4 3	6 0	5 2	4 7	4 2	5 6	4 9	4 4	4 0	5 2	4 6	4 2	3 9	3 5	
下方投影面積		c m ²	1 . 5	6 6	5 8	5 2	4 7	6 3	5 6	5 1	4 6	5 9	5 3	4 8	4 5	5 5	5 0	4 6	4 3	3 9		
			2 . 0	7 0	6 4	5 9	5 4	6 8	6 2	5 7	5 3	6 3	5 8	5 4	5 1	5 9	5 5	5 2	4 9	4 4		
等価発光面積		c m ²	2 . 5	7 3	6 8	6 3	5 9	7 1	6 6	6 1	5 8	6 6	6 2	5 8	5 5	6 2	5 8	5 5	5 3	4 8		
			3 . 0	7 5	7 0	6 6	6 2	7 3	6 8	6 4	6 1	6 8	6 5	6 1	5 8	6 4	6 1	5 8	5 6	5 1		
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	7 8	7 4	7 0	6 7	7 6	7 2	6 9	6 6	7 1	6 8	6 5	6 3	6 7	6 4	6 2	6 0	5 5		
			5 . 0	8 0	7 6	7 3	7 1	7 7	7 4	7 1	6 9	7 3	7 0	6 8	6 6	6 8	6 6	6 4	6 3	5 7		
			7 . 0	8 2	7 9	7 7	7 5	7 9	7 7	7 5	7 3	7 5	7 3	7 1	6 9	7 0	6 9	6 7	6 6	6 1		
			1 0 . 0	8 3	8 1	7 9	7 8	8 1	7 9	7 7	7 6	7 6	7 5	7 3	7 2	7 2	7 1	7 0	6 9	6 3		

