

屋内照明器具特性	
品番 (品名)	XLGE5112
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0181604 (0) DR1
BZ分類	BZ5/1.1/BZ4/6.0/BZ5/8.5/BZ4

器具効率		69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	39	31	26	22	39	31	26	22	37	30	25	22	35	29	25	22	21	
			0.6	0.8	46	39	33	29	45	38	33	29	43	37	33	29	42	36	32	29	28	
			0.56	1.0	51	44	38	35	50	43	38	34	48	42	38	34	46	41	37	34	33	
				1.25	55	48	44	40	54	48	43	40	52	47	43	39	50	45	42	39	37	
下方投影面積		cm ²		1.5	58	52	47	44	57	51	47	43	55	50	46	43	53	49	45	43	41	
等価発光面積			cm ²	2.0	62	57	53	49	60	56	52	49	58	55	51	48	56	53	50	48	46	
取付高さ	器具間隔最大限			2.5	64	60	56	53	63	59	56	53	61	58	55	52	59	56	54	52	50	
	横方向 (A)			縦方向 (B)		3.0	66	62	59	56	65	61	58	56	63	60	57	55	61	58	56	54
H m	1.23 H m	1.23 H m		4.0	68	65	62	60	67	64	62	60	65	63	60	59	63	61	59	58	56	
			5.0	69	67	64	62	68	66	64	62	66	64	63	61	64	63	61	60	58		
			7.0	70	69	67	66	70	68	66	65	68	66	65	64	66	65	64	63	61		
			10.0	72	70	69	68	71	69	68	67	69	68	67	66	67	66	66	65	63		

