

屋内照明器具特性	
品番 (品名)	LGBZ6195
光源	LED4000_70_3500 ×1 3500.0 lm
管理番号	K0179194 (0) DB 1
BZ分類	BZ5 / 1.4 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 6 7	0 . 6	5 7	4 5	3 7	3 2	5 6	4 4	3 7	3 2	5 3	4 3	3 7	3 2	5 1	4 2	3 6	3 1	3 0	
			0 . 6 3	0 . 8	6 7	5 6	4 8	4 2	6 6	5 5	4 8	4 2	6 3	5 4	4 7	4 2	6 0	5 2	4 6	4 2	4 0	
			0 . 5 6	1 . 0	7 4	6 3	5 6	5 0	7 2	6 3	5 5	5 0	6 9	6 1	5 5	5 0	6 7	5 9	5 4	4 9	4 7	
				1 . 2 5	8 0	7 0	6 3	5 8	7 8	6 9	6 3	5 7	7 5	6 8	6 2	5 7	7 2	6 6	6 1	5 6	5 4	
下方投影面積		c m ²	1 . 5	8 4	7 5	6 9	6 3	8 2	7 4	6 8	6 3	7 9	7 3	6 7	6 2	7 6	7 1	6 6	6 2	5 9		
等価発光面積			c m ²	2 . 0	9 0	8 3	7 7	7 2	8 8	8 1	7 6	7 1	8 5	7 9	7 5	7 1	8 2	7 7	7 3	7 0	6 7	
取付高さ	器具間隔最大限			2 . 5	9 3	8 7	8 2	7 8	9 2	8 6	8 1	7 7	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	7 2	
H m		1 . 2 6 H m	縦方向 (B)	3 . 0	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6	
H m		1 . 2 6 H m	4 . 0	9 9	9 5	9 1	8 8	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 1		
			5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 5		
			7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 4	9 3	9 1	8 8		
			1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2		

