

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 Y
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0180445 (0) DR 1
B Z 分類	BZ5

器具効率		52 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		5 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		47 %																								
保守率		良 中 否	0.63	0.6	28	22	18	15	27	21	18	15	26	20	17	14	24	20	16	14	13					
			0.6	0.8	33	27	23	20	32	27	23	20	30	25	22	19	28	24	21	19	17					
				1.0	37	31	27	24	36	30	26	23	33	29	25	23	31	27	25	22	20					
			0.56	1.25	40	34	30	27	38	34	30	27	36	32	29	26	34	31	28	26	24					
下方投影面積		cm ²		1.5	42	37	33	30	41	36	33	30	38	34	31	29	36	33	30	28	26					
			等価発光面積	cm ²	2.0	45	41	37	34	43	40	37	34	41	38	35	33	39	36	34	32	30				
取付 高さ	器具間隔最大限			2.5	47	43	40	37	45	42	39	37	43	40	38	36	40	38	36	34	32					
	横方向 (A)		縦方向 (B)	3.0	48	45	42	40	47	44	41	39	44	42	40	38	42	40	38	36	34					
H m	1.25 H m		1.25 H m	4.0	50	47	45	43	48	46	44	42	46	44	42	40	43	42	40	39	37					
				5.0	51	48	46	45	49	47	46	44	47	45	44	42	45	43	42	41	38					
				7.0	52	50	49	47	51	49	48	46	48	47	46	45	46	45	44	43	40					
				10.0	53	52	50	49	52	50	49	48	49	48	47	47	47	46	45	45	42					

