

屋内照明器具特性

品番 (品名)	LSEB1126														
光源	LED6200_70_4150 x1 4150.0 lm														
管理番号	K0147591(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%				
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				床	10%				10%				10%				10%				0%		
上方光束	7%																						
下方光束	93%																						
		室指数	照明率 (X0.01) ZCM																				
保守率	良 中 否	0.63	0.6	0.6	0.56	0.6	55	42	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25
		0.6	0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	34			
		1.0	1.0	71	60	52	46	69	59	51	46	65	56	50	45	62	54	48	44	41			
		0.56	1.25	77	67	59	53	75	65	58	53	71	63	57	52	67	60	55	51	47			
下方投影面積	c m ²	1.5	81	72	65	59	79	70	64	58	75	67	62	57	71	65	60	56	52				
		2.0	87	79	72	67	84	77	71	66	80	74	69	65	76	71	67	63	59				
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	84	78	74	70	80	75	71	68	64			
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	82	78	74	82	78	75	72	68			
H m	1.28 H m	1.28 H m	4.0	96	91	87	83	94	89	85	82	89	86	82	79	86	82	80	77	73			
			5.0	98	94	90	87	96	92	89	85	92	88	86	83	88	85	83	80	76			
			7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	85	80			
			10.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	89	88	83			

