

屋内照明器具特性	
品番 (品名)	F Y Y 2 6 6 6 0 J
光源	LED5000_85_3170 ×1 3170.0 lm
管理番号	K0176829 (1) DB 1
B Z 分類	B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束				1 0 0 %																					
保守率		良 中 否	0 . 7 7	0 . 6	6 3	5 3	4 6	4 1	6 2	5 2	4 6	4 1	6 0	5 1	4 5	4 1	5 8	5 0	4 5	4 1	3 9				
			0 . 7 2	0 . 8	7 4	6 4	5 7	5 2	7 2	6 3	5 7	5 2	7 0	6 2	5 6	5 2	6 8	6 1	5 6	5 2	5 0				
			0 . 6 8	1 . 0	8 0	7 1	6 5	6 0	7 9	7 0	6 4	6 0	7 6	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 7				
				1 . 2 5	8 5	7 7	7 2	6 7	8 4	7 7	7 1	6 7	8 1	7 5	7 0	6 6	7 9	7 4	6 9	6 6	6 4				
下方投影面積		c m ²	1 . 5	8 9	8 2	7 6	7 2	8 7	8 1	7 6	7 2	8 5	7 9	7 5	7 1	8 2	7 8	7 4	7 1	6 8					
			等価発光面積	c m ²	2 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 9	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 5			
取付高さ	器具間隔最大限		2 . 5	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 3	9 2	8 9	8 5	8 3	9 0	8 7	8 4	8 2	7 9					
	横方向 (A)	縦方向 (B)	3 . 0	9 8	9 4	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 6	9 2	8 9	8 7	8 5	8 2					
1 . 5 m	1 . 9 3 m	1 . 8 4 m	4 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 4	9 2	9 0	9 5	9 2	9 1	8 9	8 6					
2	2 . 5 6	2 . 3	5 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 6	9 5	9 3	9 6	9 4	9 3	9 1	8 9					
2 . 5	3 . 1 8	2 . 7 8	7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 4	9 2					
3	3 . 8	3 . 2 7	1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 8	9 8	9 7	9 4					

