

屋内照明器具特性	
品番 (品名)	L G B 8 5 0 3 9 K
光源	LED2700_70_1300 ×1 1300.0 lm
管理番号	K0179164 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.69	0.6	51	39	31	25	49	37	30	25	45	35	28	23	41	32	26	22	19
			0.67	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26
			0.63	1.0	67	55	47	41	64	53	45	40	58	49	43	38	53	46	40	36	31
				1.25	72	62	54	47	69	59	52	46	63	55	49	44	58	51	46	41	36
下方投影面積		cm ²	1.5	76	66	59	53	73	64	57	51	67	59	53	48	61	55	50	46	40	
			等価発光面積		cm ²	2.0	82	73	67	61	79	71	64	59	72	66	60	56	66	61	56
取付 高さ	器具間隔最大限		2.5	86	78	72	66	82	75	70	65	75	70	65	61	69	65	61	57	51	
	横方向 (A)	縦方向 (B)	3.0	88	82	76	71	85	79	73	69	78	73	69	65	72	68	64	61	54	
1.5m	2.06 m	1.85 m	4.0	92	86	81	77	88	83	79	75	81	77	74	70	75	72	69	66	59	
2	2.76	2.44	5.0	94	89	85	81	90	86	82	79	84	80	77	74	77	74	72	69	62	
2.5	3.46	3.04	7.0	96	93	89	86	93	89	86	84	86	83	81	79	80	78	76	74	66	
3	4.14	3.65	10.0	98	96	93	91	95	92	90	88	88	86	84	82	82	80	79	77	69	

