

屋内照明器具特性	
品番 (品名)	XLGB1118
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0186491 (0) DR 1
BZ分類	BZ5

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		3 % 76 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.67	0.6	44	34	28	24	43	34	28	24	41	33	27	23	39	32	27	23	21	
			0.63	0.8	52	42	36	32	50	42	36	31	48	40	35	31	45	39	34	31	29	
			1.0	57	48	42	37	55	47	41	37	53	46	41	36	50	44	40	36	34		
			0.56	1.25	61	54	48	43	60	53	47	43	57	51	46	42	54	49	45	41	39	
下方投影面積		cm ²	1.5	65	58	52	47	63	57	51	47	60	55	50	46	57	53	49	45	43		
等価発光面積			cm ²	2.0	69	63	58	54	68	62	57	54	65	60	56	52	62	58	54	52	49	
取付高さ				器具間隔最大限		2.5	72	67	62	59	70	66	62	58	68	63	60	57	65	61	58	56
横方向 (A)		縦方向 (B)		3.0	74	69	65	62	72	68	65	61	70	66	63	60	67	64	61	59	56	
H m	1.12 H m	1.12 H m	4.0	77	73	70	67	75	72	69	66	72	69	67	64	69	67	65	63	60		
			5.0	78	75	72	70	77	74	71	69	74	71	69	67	71	69	67	66	63		
			7.0	80	78	76	74	79	76	74	73	76	74	72	71	73	72	70	69	66		
			10.0	81	80	78	77	80	78	77	76	77	76	75	74	75	74	73	72	69		

