

屋内照明器具特性	
品番 (品名)	XLX800WHWC
光源	LED4000_85_9100 x1 9100.0lm
管理番号	K0133844(0)DR1
BZ分類	BZ6/0.7/BZ5/2.3/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	12%	床	10%				10%				10%				10%				0%			
下方光束	88%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83 中 0.81 否 0.77	0.6	53	41	33	27	51	39	32	27	48	37	31	26	44	36	30	25	22			
		0.8	62	50	42	36	60	49	41	36	56	47	40	35	52	44	38	34	30			
		1.0	69	57	49	43	66	56	48	42	62	53	46	41	58	50	44	40	36			
		1.25	74	64	56	50	72	62	55	49	67	59	53	47	63	56	50	46	42			
下方投影面積	cm <sup>2</sup>	1.5	79	69	61	55	76	67	60	54	71	63	57	52	66	60	55	51	46			
		2.0	84	76	69	63	81	74	67	62	76	70	64	60	71	66	62	58	53			
取付高さ	器具間隔最大限		2.5	88	80	74	69	85	78	73	68	80	74	69	65	75	70	66	63	58		
	横方向 (A)	縦方向 (B)	3.0	90	84	78	73	88	82	76	72	82	77	73	69	77	73	70	66	61		
1.5m	2.03m	2.86m	4.0	94	88	84	79	91	86	82	78	86	82	78	75	81	77	74	71	66		
2	2.64	3.28	5.0	96	91	87	83	93	89	85	82	88	84	81	78	83	80	77	75	69		
2.5	3.25	3.76	7.0	98	95	91	88	96	92	89	87	90	88	85	83	86	83	81	79	74		
3	3.87	4.29	10.0	100	98	95	93	98	95	93	91	93	91	89	87	88	86	84	83	77		

