

屋内照明器具特性	
品番 (品名)	L S E W C 5 0 3 9
光源	L E D 2 7 0 0 _ 7 0 _ 3 6 0 × 1 3 6 0 . 0 l m
管理番号	K 0 1 5 7 0 5 0 (0) D 1
B Z 分類	B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 5	4 1	6 2	5 2	4 5	4 1	6 0	5 1	4 5	4 0	5 8	5 0	4 4	4 0	3 9	
			0 . 6 3	0 . 8	7 4	6 4	5 7	5 2	7 2	6 3	5 7	5 2	7 0	6 2	5 6	5 2	6 8	6 1	5 6	5 2	5 0	
			0 . 5 6	1 . 0	8 0	7 2	6 5	6 1	7 9	7 1	6 5	6 0	7 6	6 9	6 4	6 0	7 4	6 8	6 3	6 0	5 8	
				1 . 2 5	8 6	7 8	7 3	6 8	8 5	7 7	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 7	6 5	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 0	8 3	7 7	7 3	8 8	8 2	7 7	7 3	8 6	8 0	7 6	7 2	8 3	7 9	7 5	7 2	7 0		
			2 . 0	9 4	8 9	8 4	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 9	7 6		
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1		
	横方向 (A)	縦方向 (B)	3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4		
H m	1 . 1 6 H m	1 . 1 9 H m	4 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 7		
			5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	9 0		
			7 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2		
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		

