

屋内照明器具特性	
品番 (品名)	L S P S C 1 0 0 L
光源	L L D 2 0 0 0 M L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 3 4 2 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		6 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 6 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	4 0	3 4	3 0	2 7	3 9	3 3	2 9	2 7	3 8	3 3	2 9	2 7	3 7	3 2	2 9	2 7	2 5		
			0 . 6	4 7	4 1	3 7	3 4	4 6	4 0	3 7	3 4	4 4	4 0	3 6	3 4	4 3	3 9	3 6	3 4	3 2		
			1 . 0	5 1	4 5	4 2	3 9	5 0	4 5	4 1	3 9	4 8	4 4	4 1	3 9	4 7	4 3	4 1	3 8	3 7		
			0 . 5 6	1 . 2 5	5 4	4 9	4 6	4 3	5 3	4 9	4 6	4 3	5 2	4 8	4 5	4 3	5 0	4 7	4 5	4 3	4 1	
下方投影面積		c m ²	1 . 5	5 6	5 2	4 9	4 6	5 5	5 1	4 9	4 6	5 4	5 0	4 8	4 6	5 2	5 0	4 7	4 5	4 4		
等価発光面積			c m ²	2 . 0	5 9	5 6	5 3	5 1	5 8	5 5	5 3	5 0	5 6	5 4	5 2	5 0	5 5	5 3	5 1	4 9	4 8	
2 . 5	6 1			5 8	5 5	5 3	6 0	5 7	5 5	5 3	5 8	5 6	5 4	5 3	5 7	5 5	5 3	5 2	5 1			
取付 高さ	器具間隔最大限			3 . 0	6 2	5 9	5 7	5 5	6 1	5 9	5 7	5 5	5 9	5 7	5 6	5 4	5 8	5 6	5 5	5 4	5 2	
	横方向 (A)	縦方向 (B)	4 . 0	6 3	6 1	6 0	5 8	6 2	6 1	5 9	5 8	6 1	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 5		
H m	1 . 1 7 H m	1 . 1 7 H m	5 . 0	6 4	6 2	6 1	6 0	6 3	6 2	6 0	5 9	6 2	6 0	5 9	5 8	6 0	5 9	5 8	5 8	5 6		
			7 . 0	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 3	6 2	6 1	6 0	6 1	6 0	6 0	5 9	5 8		
			1 0 . 0	6 6	6 5	6 4	6 3	6 5	6 4	6 3	6 3	6 3	6 3	6 2	6 2	6 2	6 1	6 1	6 0	5 9		

