

屋内照明器具特性	
品番 (品名)	XAD3 1 8 1 4
光源	LLD4 0 4 0 4 CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0183946 (0) DR 1
BZ分類	BZ1

器具効率		9 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束		9 4 %																			
保守率		良	0 . 6 7	0 . 6	7 3	6 7	6 2	5 9	7 3	6 6	6 2	5 9	7 1	6 6	6 2	5 9	7 0	6 5	6 2	5 9	5 8
		中	0 . 6 3	0 . 8	8 1	7 5	7 0	6 8	8 0	7 4	7 0	6 7	7 8	7 3	7 0	6 7	7 7	7 2	6 9	6 7	6 6
		否	0 . 5 6	1 . 0	8 5	7 9	7 6	7 3	8 4	7 9	7 5	7 3	8 2	7 8	7 5	7 2	8 1	7 7	7 4	7 2	7 1
		1 . 2 5	8 8	8 4	8 0	7 7	8 7	8 3	8 0	7 7	8 5	8 2	7 9	7 7	8 4	8 1	7 8	7 6	7 5		
下方投影面積		c m ²	1 . 5	9 0	8 6	8 3	8 1	8 9	8 6	8 3	8 0	8 8	8 4	8 2	8 0	8 6	8 3	8 1	7 9	7 8	
			等価発光面積	c m ²	2 . 0	9 3	9 0	8 7	8 5	9 2	8 9	8 7	8 5	9 0	8 8	8 6	8 4	8 9	8 6	8 5	8 3
取付 高さ	器具間隔最大限		2 . 5	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 7	9 2	9 0	8 8	8 6	9 0	8 8	8 7	8 6	8 4	
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 4	9 2	9 0	9 5	9 3	9 1	8 9	9 3	9 1	9 0	8 8	9 1	9 0	8 8	8 7	8 5	
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	9 7	9 6	9 4	9 2	9 6	9 5	9 3	9 2	9 4	9 3	9 2	9 1	9 2	9 1	9 0	8 9	8 7	
			5 . 0	9 8	9 7	9 5	9 4	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 3	9 2	9 1	9 1	8 8	
			7 . 0	9 9	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 4	9 4	9 3	9 3	9 2	9 0	
			1 0 . 0	1 0 0	9 9	9 8	9 7	9 9	9 8	9 7	9 7	9 7	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 1	

