

屋内照明器具特性

品番 (品名)	XLX430NENT									
光源	LED5000_85_3200 x1 3200.0lm									
管理番号	K0135074(6)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	4%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	96%																																																			
保守率	良 中 否	0.83	0.6	5.6	4.4	3.6	3.0	5.4	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.7																																
		0.81	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.1	5.1	4.5	4.0	5.8	5.0	4.4	3.9	3.7																																
		0.77	1.0	7.2	6.1	5.4	4.8	7.0	6.0	5.3	4.7	6.7	5.8	5.2	4.7	6.4	5.6	5.1	4.6	4.3																																
			1.25	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.2	6.5	5.9	5.4	6.9	6.2	5.7	5.3	5.0																																
下方投影面積		cm ²																																																		
等価発光面積		cm ²																																																		
取付高さ	器具間隔最大限																																																			
	横方向 (A)	縦方向 (B)																																																		
1.5m	1.94m	2.1m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.7	8.3	9.1	8.7	8.4	8.1	8.8	8.5	8.2	7.9	7.6																																
2	2.56	2.64	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.7	8.5	8.3	7.9																																
2.5	3.19	3.21	7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.1	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.7	8.3																																
3	3.8	3.79	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.3	9.4	9.3	9.1	9.0	8.6																																

