

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 5
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0190090 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 1.8 / BZ3

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29
			0.63	0.8	52	46	41	38	51	45	41	38	50	45	41	38	48	44	40	38	37
			0.56	1.0	57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41
				1.25	60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46
下方投影面積		cm ²		1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49
			等価発光面積	cm ²	2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	55
取付 高さ	器具間隔最大限			2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56
	横方向 (A) 縦方向 (B)			3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58
H m	1.31 H m 1.31 H m			4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60
				5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62
				7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64
				10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65

