

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 5
光源	L L D 5 0 2 0 L C C 1 × 1 1 0 8 5 . 0 l m
管理番号	K 0 1 9 0 1 0 8 (1) D R 1
B Z 分類	B Z 1

器具効率		81 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		ZCM
下方光束		81 %																				
保守率		良 中 否	0.67	0.6	68	63	60	58	67	63	60	58	66	62	60	58	65	62	59	58	57	
			0.63	0.8	73	69	66	64	72	68	66	64	71	68	65	64	70	67	65	63	62	
			0.56	1.0	76	72	70	68	75	72	69	68	74	71	69	67	73	70	69	67	66	
				1.25	78	75	73	71	78	75	73	71	76	74	72	70	75	73	71	70	69	
下方投影面積		c m ²		1.5	80	77	75	73	79	77	75	73	78	76	74	73	77	75	73	72	71	
			等価発光面積		c m ²	2.0	82	80	78	77	81	79	78	76	80	78	77	76	78	77	76	75
取付 高さ	器具間隔最大限		2.5	83	81	80	79	82	81	79	78	81	80	78	77	79	78	77	77	75		
	横方向 (A)	縦方向 (B)	3.0	84	83	81	80	83	82	81	80	82	81	80	79	80	79	78	78	76		
H m	0.41 H m	0.41 H m	4.0	85	84	83	82	84	83	82	81	83	82	81	80	81	80	80	79	78		
			5.0	86	85	84	83	85	84	83	83	83	82	82	81	82	81	81	80	78		
			7.0	86	86	85	85	85	85	84	84	84	83	83	83	82	82	82	81	79		
			10.0	87	86	86	86	86	86	85	85	84	84	84	84	83	82	82	82	80		

