

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 8
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0190106 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2

器具効率		90 % 上方光束 0 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	59	50	44	40	58	50	44	40	57	49	44	40	55	48	43	40	38
			0.63	0.8	69	61	55	51	68	60	55	51	66	59	54	51	64	58	54	51	49
			0.56	1.0	75	68	62	59	74	67	62	58	72	66	61	58	70	65	61	58	56
				1.25	80	73	69	65	78	73	68	65	76	71	67	64	74	70	67	64	62
下方投影面積 等価発光面積		cm ² cm ²		1.5	83	77	73	69	82	76	72	69	79	75	71	69	77	74	71	68	66
				2.0	87	82	78	75	85	81	78	75	83	80	77	74	81	78	76	74	72
				2.5	89	85	82	79	88	84	81	79	86	83	80	78	84	81	79	77	75
				3.0	90	87	84	82	89	86	84	82	87	85	82	81	85	83	81	80	78
H _m	1.28H _m	1.28H _m	4.0	92	90	88	86	91	89	87	85	89	87	85	84	87	85	84	83	81	
			5.0	94	91	90	88	92	91	89	87	90	89	87	86	88	87	86	85	82	
			7.0	95	93	92	91	94	92	91	90	92	90	89	88	90	89	88	87	85	
			10.0	96	95	94	93	95	94	93	92	93	92	91	90	91	90	89	89	86	

