

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 8
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190111 (1) DR 1
B Z 分類	BZ3 / 0.9 / BZ2 / 1.8 / BZ3

器具効率		71 % 上方光束 1 % 下方光束 70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	46	39	34	31	45	38	34	31	44	38	33	31	42	37	33	30	29
			0.63	0.8	53	46	42	39	52	46	42	39	50	45	41	38	49	44	41	38	37
			1.0	57	52	47	44	56	51	47	44	55	50	46	44	53	49	46	43	42	
			0.56	1.25	61	56	52	49	60	55	52	49	58	54	51	48	57	53	50	48	46
下方投影面積		cm ²	1.5	63	59	55	52	62	58	55	52	61	57	54	51	59	56	53	51	50	
等価発光面積			2.0	67	63	60	57	66	62	59	57	64	61	58	56	62	59	57	55	54	
取付 高さ	器具間隔最大限		2.5	68	65	62	60	67	64	62	60	66	63	61	59	64	62	60	58	57	
	横方向 (A) 縦方向 (B)		3.0	70	67	65	62	69	66	64	62	67	65	63	61	65	63	62	60	59	
H m	1.33 H m	1.33 H m	4.0	71	69	67	65	70	68	67	65	69	67	65	64	67	65	64	63	61	
			5.0	72	71	69	67	71	70	68	67	70	68	67	66	68	67	66	65	63	
			7.0	73	72	71	70	73	71	70	69	71	70	69	68	69	68	67	67	65	
			10.0	74	73	72	72	73	73	72	71	72	71	70	70	70	69	69	68	66	

