

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 9
光源	L L D 2 0 2 0 C U 1 × 1 4 6 8 . 0 l m
管理番号	K 0 1 9 0 1 0 5 (1) D R 1
B Z 分類	B Z 1

器具効率	9 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %				
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %				
上方光束	0 %	室指数	照明率 (X 0 . 0 1)																		Z C M			
下方光束	9 4 %																							
保守率	良	0 . 6 7	0 . 6	8 2	7 7	7 4	7 1	8 1	7 6	7 3	7 1	8 0	7 6	7 3	7 1	7 9	7 5	7 3	7 1	7 0				
	中	0 . 6 3	0 . 8	8 7	8 2	7 9	7 7	8 6	8 2	7 9	7 7	8 5	8 1	7 9	7 7	8 4	8 1	7 8	7 7	7 6				
	否	0 . 5 6	1 . 0	9 0	8 6	8 3	8 1	8 9	8 6	8 3	8 1	8 8	8 5	8 2	8 1	8 6	8 4	8 2	8 0	7 9				
			1 . 2 5	9 2	8 9	8 6	8 4	9 2	8 8	8 6	8 4	9 0	8 7	8 5	8 4	8 9	8 6	8 5	8 3	8 2				
下方投影面積	c m ²		1 . 5	9 4	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 2	8 9	8 7	8 6	9 0	8 8	8 7	8 5	8 4				
等価発光面積	c m ²		2 . 0	9 6	9 4	9 2	9 0	9 5	9 3	9 1	9 0	9 4	9 2	9 0	8 9	9 2	9 0	8 9	8 8	8 6				
取付 高さ	器具間隔最大限		2 . 5	9 7	9 5	9 4	9 2	9 6	9 5	9 3	9 2	9 5	9 3	9 2	9 1	9 3	9 2	9 1	9 0	8 8				
	横方向 (A)	縦方向 (B)	3 . 0	9 8	9 6	9 5	9 4	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 4	9 3	9 2	9 1	8 9				
H m	0 . 3 4 H m	0 . 3 4 H m	4 . 0	9 9	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 4	9 4	9 4	9 3	9 2	9 0				
			5 . 0	1 0 0	9 9	9 8	9 7	9 9	9 8	9 7	9 6	9 7	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 1				
			7 . 0	1 0 0	1 0 0	9 9	9 8	9 9	9 9	9 8	9 7	9 7	9 7	9 6	9 6	9 6	9 5	9 5	9 4	9 2				
			1 0 . 0	1 0 1	1 0 0	1 0 0	9 9	1 0 0	9 9	9 9	9 9	9 8	9 8	9 7	9 7	9 6	9 6	9 5	9 5	9 3				

