

屋内照明器具特性	
品番 (品名)	L G D 9 0 3 0
光源	L L D 2 4 0 0 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 3 9 (0) D B 1
B Z 分類	B Z 1

器具効率		7 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		7 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	5 3	4 7	4 3	4 1	5 3	4 7	4 3	4 1	5 1	4 6	4 3	4 0	5 0	4 6	4 3	4 0	3 9		
			0 . 8	6 0	5 4	5 1	4 8	5 9	5 4	5 1	4 8	5 8	5 3	5 0	4 8	5 6	5 3	5 0	4 8	4 7		
			1 . 0	6 4	5 9	5 6	5 3	6 3	5 9	5 5	5 3	6 1	5 8	5 5	5 3	6 0	5 7	5 4	5 2	5 1		
			0 . 5 6	1 . 2 5	6 7	6 3	6 0	5 7	6 6	6 2	5 9	5 7	6 5	6 1	5 9	5 7	6 3	6 0	5 8	5 6	5 5	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	6 9	6 5	6 2	6 0	6 8	6 5	6 2	6 0	6 6	6 4	6 1	5 9	6 5	6 3	6 1	5 9	5 8		
			2 . 0	7 1	6 8	6 6	6 4	7 1	6 8	6 6	6 4	6 9	6 7	6 5	6 3	6 7	6 6	6 4	6 2	6 1		
取付 高さ	器具間隔最大限		2 . 5	7 3	7 0	6 8	6 7	7 2	7 0	6 8	6 6	7 0	6 9	6 7	6 5	6 9	6 7	6 6	6 5	6 3		
	横方向 (A) 縦方向 (B)		3 . 0	7 4	7 2	7 0	6 8	7 3	7 1	6 9	6 8	7 1	7 0	6 8	6 7	7 0	6 9	6 7	6 6	6 5		
H m	1 . 3 0 H m	1 . 3 0 H m	4 . 0	7 5	7 4	7 2	7 1	7 4	7 3	7 1	7 0	7 3	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 7		
			5 . 0	7 6	7 5	7 3	7 2	7 5	7 4	7 3	7 2	7 3	7 2	7 1	7 1	7 2	7 1	7 0	7 0	6 8		
			7 . 0	7 7	7 6	7 5	7 4	7 6	7 5	7 4	7 3	7 4	7 4	7 3	7 2	7 3	7 2	7 2	7 1	6 9		
			1 0 . 0	7 7	7 7	7 6	7 5	7 7	7 6	7 5	7 5	7 5	7 4	7 4	7 3	7 3	7 3	7 2	7 2	7 0		

