

屋内照明器具特性	
品番 (品名)	L G D 9 0 3 1
光源	L L D 2 4 0 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 4 5 (0) D B 1
B Z 分類	B Z 1

器具効率		5 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 5	4 0	3 8	3 6	4 4	4 0	3 7	3 6	4 3	4 0	3 7	3 5	4 3	3 9	3 7	3 5	3 5
			0 . 6 3	0 . 8	5 0	4 6	4 3	4 1	4 9	4 6	4 3	4 1	4 8	4 5	4 3	4 1	4 7	4 5	4 3	4 1	4 0
			0 . 5 6	1 . 0	5 3	4 9	4 7	4 5	5 2	4 9	4 7	4 5	5 1	4 8	4 6	4 5	5 0	4 8	4 6	4 5	4 4
				1 . 2 5	5 5	5 2	5 0	4 8	5 4	5 2	5 0	4 8	5 3	5 1	4 9	4 8	5 2	5 0	4 9	4 7	4 7
下方投影面積		c m ²	1 . 5	5 6	5 4	5 2	5 0	5 6	5 3	5 2	5 0	5 5	5 3	5 1	5 0	5 3	5 2	5 0	4 9	4 8	
			等価発光面積	c m ²	2 . 0	5 8	5 6	5 4	5 3	5 7	5 6	5 4	5 3	5 6	5 5	5 3	5 2	5 5	5 4	5 3	5 2
取付 高さ	器具間隔最大限		2 . 5	5 9	5 7	5 6	5 5	5 8	5 7	5 6	5 4	5 7	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 2	
	横方向 (A)	縦方向 (B)	3 . 0	6 0	5 8	5 7	5 6	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 7	5 6	5 5	5 4	5 3	
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	6 1	6 0	5 9	5 8	6 0	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 6	5 4	
			5 . 0	6 1	6 0	5 9	5 9	6 1	6 0	5 9	5 8	5 9	5 9	5 8	5 7	5 8	5 7	5 7	5 6	5 5	
			7 . 0	6 2	6 1	6 0	6 0	6 1	6 0	6 0	5 9	6 0	5 9	5 9	5 8	5 9	5 8	5 8	5 7	5 6	
			1 0 . 0	6 2	6 2	6 1	6 1	6 1	6 1	6 1	6 0	6 0	6 0	6 0	5 9	5 9	5 9	5 8	5 8	5 7	

