

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XS Z P 3 5 0 7 V            |
| 光源       | LLD3401VCB1 ×1 700.0 lm     |
| 管理番号     | K0191393 ( 0 ) DB 1         |
| B Z 分類   | BZ3 / 1.1 / BZ2 / 1.8 / BZ3 |

| 器具効率             | 100 %<br>上方光束<br>0 %<br>下方光束<br>100 % | 天井<br>反射率<br>壁<br>床<br>室指数 | 80 %              |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |
|------------------|---------------------------------------|----------------------------|-------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|
|                  |                                       |                            | 70                | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |
|                  |                                       |                            | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |
| 保守率              | 良<br>中<br>否<br>0.69<br>0.67<br>0.63   | 0.6                        | 64                | 54  | 47  | 43  | 63   | 53  | 47  | 42  | 61   | 52  | 47  | 42  | 59   | 52  | 46 | 42 | 41  |
|                  |                                       | 0.8                        | 75                | 65  | 59  | 54  | 73   | 65  | 59  | 54  | 71   | 63  | 58  | 54  | 69   | 62  | 57 | 54 | 52  |
|                  |                                       | 1.0                        | 81                | 73  | 67  | 62  | 80   | 72  | 66  | 62  | 77   | 71  | 66  | 62  | 75   | 69  | 65 | 61 | 59  |
|                  |                                       | 1.25                       | 87                | 79  | 74  | 69  | 85   | 78  | 73  | 69  | 83   | 77  | 72  | 69  | 80   | 75  | 71 | 68 | 66  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup><br>cm <sup>2</sup>    | 1.5                        | 90                | 83  | 78  | 74  | 89   | 83  | 78  | 74  | 86   | 81  | 77  | 73  | 84   | 79  | 76 | 73 | 71  |
|                  |                                       | 2.0                        | 95                | 89  | 85  | 81  | 93   | 88  | 84  | 81  | 91   | 87  | 83  | 80  | 88   | 85  | 82 | 79 | 77  |
|                  |                                       | 2.5                        | 97                | 93  | 89  | 86  | 96   | 92  | 88  | 85  | 94   | 90  | 87  | 84  | 91   | 88  | 86 | 83 | 81  |
|                  |                                       | 3.0                        | 99                | 95  | 92  | 89  | 98   | 94  | 91  | 88  | 95   | 92  | 90  | 87  | 93   | 91  | 88 | 86 | 84  |
| 取付<br>高さ<br>Hm   | 器具間隔最大限                               |                            | 4.0               | 102 | 99  | 96  | 93   | 100 | 97  | 95  | 93   | 98  | 95  | 93  | 91   | 95  | 94 | 92 | 90  |
|                  | 横方向 ( A )                             | 縦方向 ( B )                  | 5.0               | 103 | 100 | 98  | 96   | 102 | 99  | 97  | 95   | 99  | 97  | 96  | 94   | 97  | 95 | 94 | 92  |
|                  | 1.33Hm                                | 1.33Hm                     | 7.0               | 104 | 103 | 101 | 99   | 103 | 102 | 100 | 98   | 101 | 99  | 98  | 97   | 99  | 97 | 96 | 95  |
|                  |                                       |                            | 10.0              | 106 | 104 | 103 | 102  | 104 | 103 | 102 | 101  | 102 | 101 | 100 | 99   | 100 | 99 | 98 | 97  |

