

屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (
光源	HF200X/N x1 9900.0 lm														
管理番号	K0038123 (*) DJ 1														
BZ分類	BZ1/4.5/BZ2/6.0/BZ1														

器具効率	80%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	80%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.73	0.6	5.7	5.0	4.5	4.2	5.6	5.0	4.5	4.2	5.5	4.9	4.5	4.2	5.4	4.8	4.5	4.2	4.1
		0.69	0.8	6.4	5.8	5.4	5.1	6.3	5.7	5.3	5.0	6.2	5.7	5.3	5.0	6.0	5.6	5.3	5.0	4.9
			1.0	6.9	6.3	5.9	5.6	6.8	6.3	5.9	5.6	6.6	6.2	5.8	5.6	6.4	6.1	5.8	5.5	5.4
		0.61	1.25	7.2	6.7	6.4	6.1	7.1	6.7	6.3	6.1	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	5.8
下方投影面積	c m ²	1.5	7.5	7.0	6.7	6.4	7.4	7.0	6.7	6.4	7.2	6.9	6.6	6.4	7.0	6.7	6.5	6.3	6.2	
		2.0	7.8	7.4	7.1	6.9	7.7	7.4	7.1	6.9	7.5	7.2	7.0	6.8	7.3	7.1	6.9	6.7	6.6	
取付高さ	器具間隔最大限		2.5	8.0	7.7	7.4	7.2	7.9	7.6	7.4	7.2	7.7	7.5	7.3	7.1	7.5	7.3	7.2	7.0	
	横方向 (A)	縦方向 (B)	3.0	8.1	7.8	7.6	7.4	8.0	7.7	7.5	7.4	7.8	7.6	7.4	7.3	7.6	7.5	7.3	7.2	
H m	0.74 H m	0.74 H m	4.0	8.2	8.0	7.9	7.7	8.1	7.9	7.8	7.6	7.9	7.8	7.7	7.5	7.8	7.6	7.5	7.4	
			5.0	8.3	8.2	8.0	7.9	8.2	8.1	7.9	7.8	8.0	7.9	7.8	7.7	7.9	7.8	7.7	7.6	
			7.0	8.4	8.3	8.2	8.1	8.3	8.2	8.1	8.0	8.1	8.0	8.0	7.9	8.0	7.9	7.8	7.7	
			10.0	8.5	8.4	8.3	8.2	8.4	8.3	8.2	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.9	7.7	

