

屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (
光源	MF400.L-J2/BU-PS ×1 42000.0 lm										
管理番号	K0106927 (0) DB1										
BZ分類	BZ1										

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	2 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	76 %																																																			
保守率	良 中 否	0.5	0.6	59	53	49	46	58	53	49	46	57	52	49	46	56	51	48	46	45																																
		0.47	0.8	65	60	56	53	64	59	56	53	63	58	55	53	61	58	55	53	51																																
		0.42	1.0	69	64	61	58	68	63	60	58	66	62	60	57	65	61	59	57	56																																
			1.25	72	68	65	62	71	67	64	62	69	66	63	61	68	65	63	61	59																																
下方投影面積	c m ²	1.5	74	70	67	65	73	69	67	65	71	68	66	64	69	67	65	63	62																																	
		2.0	76	73	71	69	75	73	70	68	73	71	69	68	72	70	68	67	65																																	
取付高さ	器具間隔最大限		2.5	78	75	73	71	77	74	73	71	75	73	71	70	73	72	70	69	67																																
	横方向 (A)	縦方向 (B)	3.0	79	77	75	73	78	76	74	73	76	74	73	71	74	73	72	70	69																																
H m	0.90 H m	0.90 H m	4.0	80	78	77	75	79	77	76	75	77	76	75	74	75	74	73	72	70																																
			5.0	81	79	78	77	80	78	77	76	78	77	76	75	76	75	74	74	74	71																															
			7.0	82	81	80	79	81	80	79	78	79	78	77	76	77	76	76	75	73																																
			10.0	82	82	81	80	81	81	80	79	79	79	78	78	77	77	76	76	74																																

