

屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (
光源	NH220FTW.L ×1 26500.0 lm		
管理番号	K0106929 (0) DB1		
BZ分類	BZ1		

器具効率	80%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	1%	反射率	10%				10%				10%				10%				0%	
下方光束	79%		10%				10%				10%				10%				0%	
		室指数	照明率 (×0.01)																ZCM	
保守率	良 0.78	0.6	58	52	47	44	58	51	47	44	56	51	47	44	55	50	46	44	43	
	中 0.74	0.8	65	59	55	52	64	59	55	52	63	58	54	52	61	57	54	52	50	
	否 0.65	1.0	69	64	60	57	68	64	60	57	67	63	59	57	65	62	59	57	55	
下方投影面積	cm ²	1.25	73	68	65	62	72	68	64	62	70	66	64	61	68	65	63	61	59	
		1.5	75	71	68	65	74	70	67	65	72	69	67	64	71	68	66	64	62	
等価発光面積	cm ²	2.0	78	75	72	70	77	74	71	69	75	73	70	69	73	71	69	68	66	
		2.5	80	77	75	73	79	76	74	72	77	75	73	71	75	73	72	70	69	
取付高さ	器具間隔最大限		3.0	81	78	76	75	80	78	76	74	78	76	74	73	76	75	73	72	70
	横方向 (A)	縦方向 (B)	4.0	82	80	79	77	81	79	78	77	79	78	77	75	77	76	75	74	72
Hm	0.59Hm	0.59Hm	5.0	83	81	80	79	82	81	79	78	80	79	78	77	78	77	76	76	73
			7.0	84	83	82	81	83	82	81	80	81	80	79	79	79	78	78	77	75
			10.0	85	84	83	82	84	83	82	81	82	81	80	80	80	79	79	78	76

