

# 屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (	
光源	MF400L / BUSC / N ×1	36500.0 lm
管理番号	K0038131 (* ) DJ 1	
BZ分類	BZ1	

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	78 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.5	0.6	58	52	48	45	57	51	48	45	56	51	47	45	55	50	47	45	44			
	中	0.47	0.8	65	59	55	52	64	58	55	52	62	58	54	52	61	57	54	52	51			
	否	0.42	1.0	69	63	60	57	68	63	60	57	66	62	59	57	65	61	59	56	55			
			1.25	72	67	64	61	71	67	64	61	69	66	63	61	68	65	62	60	59			
下方投影面積		cm <sup>2</sup>	1.5	74	70	67	64	73	69	66	64	71	68	66	64	70	67	65	63	62			
等価発光面積		cm <sup>2</sup>	2.0	77	73	71	69	76	73	70	68	74	71	69	68	72	70	68	67	65			
取付高さ	器具間隔最大限		2.5	78	76	73	71	77	75	73	71	76	73	72	70	74	72	71	69	68			
	横方向 (A)	縦方向 (B)	3.0	79	77	75	73	78	76	74	73	77	75	73	72	75	73	72	71	69			
Hm	0.92Hm	0.92Hm	4.0	81	79	77	76	80	78	77	75	78	77	75	74	76	75	74	73	71			
			5.0	81	80	79	77	80	79	78	77	79	78	77	76	77	76	75	74	73			
			7.0	82	81	80	79	81	80	79	79	80	79	78	77	78	77	77	76	74			
			10.0	83	82	81	81	82	81	81	80	80	80	79	79	79	78	78	77	75			

