

# 屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (														
光源	MF300L / BUSC-P / N ×1 25500.0 lm														
管理番号	K0038128 (*) DJ 1														
BZ分類	BZ1														

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 ( X0.01)																ZCM		
下方光束	78 %																				
保守率	良 中 否 0.5 0.47 0.42	0.6	58	52	48	45	58	52	48	45	56	51	48	45	55	51	47	45	44		
		0.8	65	59	55	52	64	59	55	52	62	58	55	52	61	57	54	52	51		
		1.0	68	63	60	57	68	63	60	57	66	62	59	57	65	61	59	56	55		
		1.25	72	67	64	61	71	67	64	61	69	66	63	61	68	65	62	60	59		
下方投影面積	c m <sup>2</sup>	1.5	74	70	67	64	73	69	66	64	71	68	66	64	70	67	65	63	62		
		2.0	76	73	71	68	75	73	70	68	74	71	69	67	72	70	68	67	65		
取付高さ	器具間隔最大限		2.5	78	75	73	71	77	75	72	71	75	73	71	70	74	72	70	69	68	
	横方向 (A)	縦方向 (B)	3.0	79	77	75	73	78	76	74	73	76	75	73	72	75	73	72	71	69	
H m	0.86 H m	0.86 H m	4.0	80	79	77	75	79	78	76	75	78	76	75	74	76	75	74	73	71	
			5.0	81	80	78	77	80	79	78	76	78	77	76	75	77	76	75	74	72	
			7.0	82	81	80	79	81	80	79	78	79	78	78	77	78	77	76	76	74	
			10.0	83	82	81	80	82	81	80	80	80	79	79	78	78	77	77	75		

