

屋内照明器具特性

品番 (品名)	HSR1M-180-400 (CML, M, NH) (
光源	MF250L / BUSC / N x1	20000.0 lm
管理番号	K0038125 (*) DJ 1	
BZ分類	BZ1	

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30		10			
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	79 %		室指数	照明率 (X0.01)																			
保守率	良 0.5	0.6	64	58	55	52	63	58	54	52	62	57	54	52	61	57	54	52	51				
	中 0.47	0.8	69	64	61	58	68	64	61	58	67	63	60	58	66	62	60	58	57				
	否 0.42	1.0	72	68	65	63	72	68	65	63	70	67	64	62	69	66	64	62	61				
		1.25	75	71	69	66	74	71	68	66	73	70	68	66	71	69	67	65	64				
下方投影面積	c m ²	1.5	77	74	71	69	76	73	71	69	75	72	70	68	73	71	69	68	66				
		2.0	79	76	74	72	78	76	74	72	77	75	73	71	75	73	72	71	69				
取付高さ	器具間隔最大限		2.5	81	78	76	75	80	78	76	74	78	76	75	73	76	75	74	73	71			
	横方向 (A)	縦方向 (B)	3.0	81	79	78	76	81	79	77	76	79	77	76	75	77	76	75	74	72			
H m	0.75 H m	0.75 H m	4.0	83	81	80	78	82	80	79	78	80	79	78	77	78	77	76	74				
			5.0	83	82	81	80	82	81	80	79	81	80	79	78	79	78	77	75				
			7.0	84	83	82	81	83	82	81	81	81	81	80	79	80	79	79	76				
			10.0	85	84	83	83	84	83	82	82	82	81	81	80	80	80	79	77				

