

# 屋内照明器具特性

品番 (品名)	HSR1M-660-1K(M, NH) (YK363)				
光源	HF700X/N ×1      41000.0 lm				
管理番号	K0038204(*)DJ1				
BZ分類	BZ2/0.9/BZ1/1.4/BZ2/8.5/BZ1				

器具効率	80%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	10%				10%				10%				10%				0%				
下方光束	80%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01)																				ZCM
保守率	良	0.73	0.6	57	50	45	42	56	49	45	42	54	48	44	42	53	48	44	41	40			
	中	0.69	0.8	64	58	53	50	63	57	53	50	61	56	52	50	60	55	52	49	48			
	否	0.61	1.0	69	63	59	56	68	62	58	55	66	61	58	55	64	60	57	55	54			
			1.25	72	67	63	61	71	67	63	60	69	66	62	60	68	64	62	60	58			
下方投影面積			1.5	75	70	67	64	74	70	66	64	72	68	65	63	70	67	65	63	61			
等価発光面積			2.0	78	74	71	69	77	73	71	68	75	72	70	68	73	71	69	67	65			
取付高さ	器具間隔最大限		2.5	80	77	74	72	79	76	73	71	77	74	72	71	75	73	71	70	68			
	横方向 (A)	縦方向 (B)	3.0	81	78	76	74	80	77	75	74	78	76	74	73	76	75	73	72	70			
Hm	0.95Hm	0.95Hm	4.0	82	80	78	77	81	79	78	76	79	78	77	75	78	76	75	74	72			
			5.0	83	82	80	79	82	81	79	78	80	79	78	77	79	78	77	76	74			
			7.0	84	83	82	81	83	82	81	80	81	81	80	79	80	79	78	78	75			
			10.0	85	84	83	83	84	83	82	82	82	82	81	80	80	80	79	79	77			

