

# 屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (										
光源	MF400CL/BU/360/N ×1 43200.0 lm										
管理番号	K0108351 (1) DB1										
BZ分類	BZ2/8.5/BZ1										

器具効率	80%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	79%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	5.5	4.7	4.2	3.9	5.4	4.7	4.2	3.9	5.2	4.6	4.2	3.8	5.1	4.5	4.1	3.8	3.7
	中	0.65	0.8	6.2	5.6	5.1	4.8	6.1	5.5	5.1	4.8	6.0	5.4	5.0	4.7	5.8	5.3	5.0	4.7	4.6
	否	0.58	1.0	6.7	6.1	5.7	5.4	6.6	6.1	5.7	5.4	6.4	6.0	5.6	5.3	6.3	5.9	5.5	5.3	5.1
			1.25	7.1	6.6	6.2	5.9	7.0	6.5	6.2	5.9	6.8	6.4	6.1	5.8	6.6	6.3	6.0	5.8	5.6
下方投影面積		cm <sup>2</sup>	1.5	7.4	6.9	6.6	6.3	7.3	6.8	6.5	6.2	7.1	6.7	6.4	6.2	6.9	6.6	6.3	6.1	6.0
等価発光面積		cm <sup>2</sup>	2.0	7.7	7.3	7.0	6.8	7.6	7.2	7.0	6.7	7.4	7.1	6.9	6.7	7.2	7.0	6.7	6.6	6.4
取付高さ	器具間隔最大限		2.5	7.9	7.6	7.3	7.1	7.8	7.5	7.3	7.0	7.6	7.3	7.1	6.9	7.4	7.2	7.0	6.9	6.7
	横方向 (A)	縦方向 (B)	3.0	8.0	7.7	7.5	7.3	7.9	7.7	7.4	7.3	7.7	7.5	7.3	7.2	7.5	7.3	7.2	7.0	6.9
Hm	1.28Hm	1.28Hm	4.0	8.2	8.0	7.8	7.6	8.1	7.9	7.7	7.5	7.9	7.7	7.6	7.4	7.7	7.5	7.4	7.3	7.1
			5.0	8.3	8.1	7.9	7.8	8.1	8.0	7.9	7.7	7.9	7.8	7.7	7.6	7.8	7.6	7.5	7.5	7.2
			7.0	8.4	8.2	8.1	8.0	8.3	8.1	8.0	7.9	8.0	8.0	7.9	7.8	7.9	7.8	7.7	7.6	7.4
			10.0	8.4	8.3	8.3	8.2	8.3	8.3	8.2	8.1	8.1	8.1	8.0	7.9	7.9	7.9	7.8	7.8	7.5

