

屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (
光源	NH110F.L x1 10600.0 lm														
管理番号	K0038134 (*) DJ 1														
BZ分類	BZ2/0.9/BZ1/4.5/BZ2/6.0/BZ1														

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	81 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)															ZCM		
保守率	良 中 否	0.78	0.6	57	49	45	41	56	49	44	41	54	48	44	41	53	48	44	41	40
		0.74	0.8	65	58	54	50	64	58	53	50	62	57	53	50	61	56	53	50	49
			1.0	70	64	60	57	69	63	59	56	67	62	59	56	65	61	58	56	55
		0.65	1.25	74	69	65	62	73	68	64	62	71	67	64	61	69	66	63	61	59
下方投影面積	c m ²	1.5	76	72	68	65	75	71	68	65	73	70	67	65	71	69	66	64	63	
		2.0	79	76	73	70	78	75	72	70	76	73	71	69	75	72	70	68	67	
取付高さ	器具間隔最大限		2.5	81	78	75	73	80	77	75	73	78	76	74	72	76	74	73	71	70
	横方向 (A)	縦方向 (B)	3.0	82	80	77	75	81	79	77	75	79	77	76	74	78	76	74	73	71
H m	1.27 H m	1.27 H m	4.0	84	82	80	78	83	81	79	78	81	79	78	77	79	78	77	76	74
			5.0	85	83	81	80	84	82	81	80	82	81	79	78	80	79	78	77	75
			7.0	86	84	83	82	85	84	83	82	83	82	81	80	81	80	80	79	77
			10.0	86	86	85	84	85	85	84	83	84	83	82	82	82	81	81	80	78

