

屋内照明器具特性	
品番 (品名)	HSR1W-180-400 (CML, M, NH) (
光源	MF400.L-J2/BU-PS ×1 42000.0 lm
管理番号	K0106938 (0) DB1
BZ分類	BZ2/1.1/BZ1/1.4/BZ2/2.3/BZ1 /3.5/BZ2/8.5/BZ1

器具効率	80%	天井	80%				70%				50%				30%				0%		
	上方光束 1%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 79%	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.5 0.47 0.42	0.6	55	48	43	40	54	47	43	39	53	46	42	39	51	46	42	39	38		
		0.8	63	56	52	49	62	56	51	48	60	55	51	48	58	54	50	48	46		
		1.0	68	62	58	54	67	61	57	54	65	60	57	54	63	59	56	54	52		
		1.25	71	66	63	60	70	66	62	59	68	64	61	59	67	63	61	58	57		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	74	69	66	63	73	69	65	63	71	67	65	62	69	66	64	62	60		
		2.0	77	73	70	68	76	73	70	68	74	71	69	67	72	70	68	66	64		
取付 高さ H m	器具間隔最大		2.5	79	76	73	71	78	75	73	71	76	73	71	70	74	72	70	69	67	
	横方向 (A) 1.25 H m	縦方向 (B) 1.25 H m	3.0	80	77	75	73	79	77	75	73	77	75	73	72	75	73	72	71	69	
			4.0	82	80	78	76	81	79	77	76	78	77	76	74	77	75	74	73	71	
			5.0	83	81	79	78	81	80	79	77	79	78	77	76	77	76	75	75	72	
			7.0	84	82	81	80	82	81	80	79	80	79	79	78	78	78	77	76	74	
			10.0	84	83	83	82	83	82	82	81	81	80	80	79	79	79	78	78	75	

