

# 屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (														
光源	MF250.L-J2/BU-PS ×1 22000.0 1 m														
管理番号	K0106935 (0) DB 1														
BZ分類	BZ1														

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	1 %	室指数																		
下方光束	78 %	照明率 ( X0.01 )																		
		ZCM																		
保守率	良 0.5 中 0.47 否 0.42	0.6	58	51	47	44	57	51	47	44	55	50	46	44	54	49	46	44	42	
		0.8	65	59	55	52	64	58	55	52	62	58	54	52	61	57	54	52	50	
		1.0	69	64	60	58	68	63	60	57	66	62	59	57	65	61	59	57	55	
		1.25	72	68	65	62	71	67	64	62	70	66	63	61	68	65	63	61	59	
下方投影面積	c m <sup>2</sup>	1.5	74	71	68	65	73	70	67	65	72	69	66	64	70	67	65	64	62	
		2.0	77	74	71	69	76	73	71	69	74	72	70	68	72	70	69	67	66	
取付高さ	器具間隔最大限		2.5	79	76	74	72	78	75	73	72	76	74	72	71	74	72	71	70	68
	横方向 (A)	縦方向 (B)	3.0	80	78	76	74	79	77	75	73	77	75	74	72	75	74	72	71	69
H m	1.21 H m	1.21 H m	4.0	81	79	78	76	80	78	77	76	78	77	76	74	76	75	74	73	71
			5.0	82	80	79	78	81	79	78	77	79	78	77	76	77	76	75	75	72
			7.0	83	82	81	80	82	81	80	79	80	79	78	77	78	77	77	76	74
			10.0	83	83	82	81	82	82	81	80	80	80	79	79	78	78	77	77	75

