

屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (
光源	MF400L / BUSC / N x1 36500.0 lm				
管理番号	K0037347 (*) DJ 1				
BZ分類	BZ3 / 0.7 / BZ2				

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	0 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	78 %																																																			
保守率	良 中 否	0.5	0.6	52	44	39	35	51	43	39	35	49	43	38	35	48	42	38	35	34																																
		0.47	0.8	60	53	48	45	59	52	48	44	57	51	47	44	55	51	47	44	43																																
		0.42	1.0	65	59	54	51	64	58	54	51	62	57	53	50	60	56	53	50	49																																
			1.25	69	63	59	56	68	63	59	56	66	62	58	56	64	61	58	55	54																																
下方投影面積	c m ²	1.5	71	67	63	60	70	66	63	60	68	65	62	59	67	64	61	59	57																																	
		2.0	75	71	68	65	74	70	67	65	72	69	66	64	70	68	65	64	62																																	
取付高さ	器具間隔最大限		2.5	77	73	71	69	76	73	70	68	74	71	69	67	72	70	68	67	65																																
	横方向 (A)	縦方向 (B)	3.0	78	75	73	71	77	74	72	70	75	73	71	69	73	72	70	69	67																																
H m	1.36 H m	1.36 H m	4.0	80	77	76	74	79	77	75	73	77	75	74	72	75	74	72	71	69																																
			5.0	81	79	77	76	80	78	77	75	78	76	75	74	76	75	74	73	71																																
			7.0	82	80	79	78	81	80	78	77	79	78	77	76	77	76	76	75	73																																
			10.0	82	82	81	80	81	81	80	79	80	79	78	78	78	77	77	76	74																																

