

屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (
光源	MF300L / BUSC-P/N ×1 25500.0 lm				
管理番号	K0038140 (*) DJ 1				
BZ分類	BZ2				

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	79 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.5	0.6	53	46	41	38	53	45	41	37	51	45	40	37	50	44	40	37	36	
	中 0.47	0.8	61	55	50	47	60	54	50	46	59	53	49	46	57	52	49	46	45	
	否 0.42	1.0	66	60	56	53	65	60	56	52	63	59	55	52	62	58	54	52	51	
		1.25	70	65	61	58	69	64	61	58	67	63	60	57	66	62	59	57	56	
下方投影面積	c m ²	1.5	73	68	64	62	72	67	64	61	70	66	63	61	68	65	62	60	59	
		2.0	76	72	69	67	75	72	69	66	73	70	68	66	71	69	67	65	63	
取付高さ	器具間隔最大限		2.5	78	75	72	70	77	74	72	69	75	73	71	69	73	71	70	68	
	横方向 (A)	縦方向 (B)	3.0	79	77	74	72	78	76	74	72	76	74	72	71	75	73	71	70	68
H m	1.22 H m	1.22 H m	4.0	81	79	77	75	80	78	76	75	78	76	75	74	76	75	74	73	71
			5.0	82	80	78	77	81	79	78	76	79	78	76	75	77	76	75	74	72
			7.0	83	82	80	79	82	81	80	79	80	79	78	77	78	77	77	76	74
			10.0	84	83	82	81	83	82	81	80	81	80	79	79	79	79	78	77	75

