

屋内照明器具特性

品番 (品名)	HSR1W-180-400 (CML, M, NH) (
光源	MF250L / BUSC / N x1 20000.0 lm														
管理番号	K0038137 (*) DJ 1														
BZ分類	BZ2 / 1.1 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1														

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	81 %	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.5	0.6	5.6	4.8	4.4	4.0	5.5	4.8	4.3	4.0	5.4	4.7	4.3	4.0	5.2	4.7	4.3	4.0	3.9
	中	0.47	0.8	6.4	5.7	5.3	5.0	6.3	5.7	5.3	4.9	6.1	5.6	5.2	4.9	6.0	5.5	5.2	4.9	4.8
	否	0.42	1.0	6.9	6.3	5.9	5.6	6.8	6.2	5.8	5.6	6.6	6.1	5.8	5.5	6.4	6.0	5.7	5.5	5.4
			1.25	7.3	6.8	6.4	6.1	7.2	6.7	6.3	6.1	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	5.8
下方投影面積			1.5	7.5	7.1	6.7	6.4	7.4	7.0	6.7	6.4	7.2	6.9	6.6	6.4	7.1	6.8	6.5	6.3	6.2
			2.0	7.8	7.5	7.2	6.9	7.7	7.4	7.1	6.9	7.5	7.3	7.0	6.8	7.4	7.1	6.9	6.8	6.6
取付高さ	器具間隔最大限		2.5	8.0	7.7	7.5	7.2	7.9	7.6	7.4	7.2	7.7	7.5	7.3	7.1	7.6	7.4	7.2	7.0	6.9
	横方向 (A)	縦方向 (B)	3.0	8.1	7.9	7.7	7.5	8.0	7.8	7.6	7.4	7.8	7.6	7.5	7.3	7.7	7.5	7.4	7.2	7.1
Hm	1.32Hm	1.32Hm	4.0	8.3	8.1	7.9	7.7	8.2	8.0	7.8	7.7	8.0	7.8	7.7	7.6	7.8	7.7	7.6	7.5	7.3
			5.0	8.4	8.2	8.1	7.9	8.3	8.1	8.0	7.9	8.1	8.0	7.8	7.7	7.9	7.8	7.7	7.6	7.4
			7.0	8.5	8.4	8.2	8.1	8.4	8.3	8.2	8.1	8.2	8.1	8.0	7.9	8.0	7.9	7.9	7.8	7.6
			10.0	8.5	8.5	8.4	8.3	8.5	8.4	8.3	8.2	8.3	8.2	8.1	8.1	8.1	8.0	8.0	7.9	7.7

