

# 屋内照明器具特性

品番 (品名)	HSR1W-660-1K(M, NH) (YK363)	
光源	MF700L / BUSC / N x1	70000.0 lm
管理番号	K0038214 (* ) DJ 1	
BZ分類	BZ3 / 1.1 / BZ2	

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %
下方光束	82 %	室指数	照明率 ( X0.01 )																ZCM
保守率	良 0.5	0.6	5.2	4.3	3.8	3.4	5.1	4.3	3.7	3.4	4.9	4.2	3.7	3.3	4.8	4.1	3.7	3.3	3.2
	中 0.47	0.8	6.1	5.3	4.8	4.4	6.0	5.3	4.8	4.4	5.8	5.2	4.7	4.4	5.6	5.1	4.7	4.4	4.2
	否 0.42	1.0	6.7	6.0	5.5	5.1	6.6	5.9	5.5	5.1	6.4	5.8	5.4	5.1	6.2	5.7	5.3	5.0	4.9
		1.25	7.1	6.5	6.1	5.7	7.0	6.5	6.1	5.7	6.8	6.4	6.0	5.7	6.6	6.2	5.9	5.6	5.5
下方投影面積	c m <sup>2</sup>	1.5	7.4	6.9	6.5	6.2	7.3	6.8	6.4	6.1	7.1	6.7	6.4	6.1	6.9	6.6	6.3	6.0	5.9
等価発光面積		2.0	7.8	7.4	7.0	6.7	7.7	7.3	7.0	6.7	7.5	7.2	6.9	6.6	7.3	7.0	6.8	6.6	6.4
取付高さ		2.5	8.0	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.5	7.2	7.0	7.5	7.3	7.1	6.9	6.7
H m		3.0	8.2	7.9	7.6	7.4	8.1	7.8	7.6	7.3	7.9	7.6	7.4	7.2	7.7	7.5	7.3	7.2	7.0
		4.0	8.4	8.1	7.9	7.7	8.3	8.1	7.9	7.7	8.1	7.9	7.7	7.6	7.9	7.7	7.6	7.5	7.3
		5.0	8.5	8.3	8.1	8.0	8.4	8.2	8.0	7.9	8.2	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.4
		7.0	8.6	8.5	8.3	8.2	8.5	8.4	8.3	8.1	8.3	8.2	8.1	8.0	8.1	8.0	8.0	7.9	7.7
		10.0	8.7	8.6	8.5	8.4	8.6	8.5	8.4	8.3	8.4	8.3	8.3	8.2	8.2	8.2	8.1	8.0	7.8

