

# 屋内照明器具特性

品番 (品名)	HSR1W-660-1K(M, NH) (YK363)				
光源	HF700X/N ×1      41000.0 lm				
管理番号	K0038213 (* ) DJ 1				
BZ分類	BZ4/0.7/BZ3/8.5/BZ2				

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	反射率	床		10 %		10 %		10 %		10 %		10 %		10 %		0 %				
下方光束	81 %		室指数																		
		照明率 ( X0.01 )																		ZCM	
保守率	良	0.73	0.6	5.0	4.1	3.5	3.1	4.9	4.1	3.5	3.1	4.7	4.0	3.5	3.1	4.6	3.9	3.4	3.1	3.0	
	中	0.69	0.8	5.9	5.1	4.6	4.2	5.8	5.0	4.5	4.1	5.6	4.9	4.5	4.1	5.4	4.9	4.4	4.1	4.0	
	否	0.61	1.0	6.5	5.8	5.2	4.9	6.4	5.7	5.2	4.8	6.2	5.6	5.2	4.8	6.0	5.5	5.1	4.8	4.6	
			1.25	6.9	6.3	5.8	5.5	6.8	6.2	5.8	5.5	6.6	6.1	5.7	5.4	6.4	6.0	5.7	5.4	5.2	
下方投影面積			1.5	7.2	6.7	6.3	5.9	7.1	6.6	6.2	5.9	6.9	6.5	6.1	5.8	6.7	6.4	6.0	5.8	5.6	
等価発光面積			2.0	7.6	7.2	6.8	6.5	7.5	7.1	6.8	6.5	7.3	7.0	6.7	6.4	7.1	6.8	6.6	6.4	6.2	
取付高さ	器具間隔最大限		2.5	7.9	7.5	7.2	6.9	7.8	7.4	7.1	6.9	7.5	7.3	7.0	6.8	7.4	7.1	6.9	6.7	6.5	
	横方向 (A)	縦方向 (B)	3.0	8.0	7.7	7.4	7.2	7.9	7.6	7.4	7.1	7.7	7.5	7.2	7.0	7.5	7.3	7.1	7.0	6.8	
Hm	1.45Hm	1.45Hm	4.0	8.2	8.0	7.7	7.5	8.1	7.9	7.7	7.5	7.9	7.7	7.5	7.4	7.7	7.5	7.4	7.3	7.1	
			5.0	8.3	8.1	7.9	7.8	8.2	8.0	7.9	7.7	8.0	7.9	7.7	7.6	7.8	7.7	7.6	7.5	7.3	
			7.0	8.4	8.3	8.2	8.0	8.3	8.2	8.1	8.0	8.1	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.5	
			10.0	8.5	8.4	8.3	8.2	8.4	8.3	8.2	8.2	8.2	8.2	8.1	8.0	8.1	8.0	7.9	7.9	7.6	

