

屋内照明器具特性	
品番 (品名)	J L 1 5 5 1 0 Z
光源	L W 1 0 0 V 2 0 0 W × 1 3 3 3 0 . 0 1 m
管理番号	K 0 0 9 9 2 5 5 (*) D B 1
B Z 分類	B Z 9

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	42 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	47 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X 0 . 0 1)																Z C M	
保守率	良	0.89	0.6	3.9	2.8	2.1	1.6	3.6	2.6	1.9	1.5	3.0	2.2	1.6	1.2	2.4	1.8	1.3	1.0	6
	中	0.84	0.8	4.7	3.6	2.8	2.2	4.3	3.3	2.6	2.1	3.5	2.8	2.2	1.8	2.9	2.3	1.8	1.5	9
	否	0.79	1.0	5.2	4.1	3.3	2.8	4.7	3.8	3.1	2.6	3.9	3.2	2.6	2.2	3.2	2.6	2.2	1.8	11
			1.25	5.7	4.7	3.9	3.3	5.2	4.3	3.6	3.1	4.3	3.6	3.1	2.6	3.5	3.0	2.5	2.2	14
下方投影面積	cm ²	1.5	6.0	5.1	4.3	3.7	5.5	4.7	4.0	3.5	4.6	3.9	3.4	3.0	3.8	3.2	2.8	2.5	1.6	
等価発光面積	cm ²	2.0	6.5	5.7	5.0	4.4	6.0	5.3	4.6	4.1	5.0	4.4	4.0	3.5	4.1	3.7	3.3	2.9	2.0	
取付高さ	器具間隔最大限		2.5	6.9	6.1	5.5	4.9	6.3	5.7	5.1	4.6	5.3	4.8	4.3	3.9	4.4	4.0	3.6	3.3	2.3
	横方向 (A)	縦方向 (B)	3.0	7.1	6.4	5.8	5.3	6.6	6.0	5.4	5.0	5.5	5.1	4.6	4.3	4.6	4.2	3.9	3.6	2.5
H _m	1.56 H _m	1.56 H _m	4.0	7.4	6.9	6.4	5.9	6.9	6.4	5.9	5.5	5.8	5.4	5.1	4.7	4.8	4.5	4.2	4.0	2.8
			5.0	7.6	7.1	6.7	6.3	7.1	6.6	6.2	5.9	6.0	5.7	5.4	5.1	5.0	4.8	4.5	4.3	3.1
			7.0	7.9	7.5	7.1	6.8	7.3	7.0	6.7	6.4	6.3	6.0	5.7	5.5	5.3	5.0	4.8	4.6	3.4
			10.0	8.1	7.8	7.5	7.2	7.5	7.3	7.0	6.8	6.5	6.2	6.0	5.9	5.5	5.3	5.1	5.0	3.7

