

屋内照明器具特性	
品番 (品名)	XSZR3000N
光源	LLD3400NCB1 ×1 700.0 lm
管理番号	K0192054 (0) DB 1
BZ分類	BZ2

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	48	42	38	35	48	41	37	35	46	41	37	35	45	40	37	35	33
			0.6	0.8	55	49	45	42	54	48	45	42	52	48	44	42	51	47	44	42	40
			0.56	1.0	59	53	50	47	58	53	49	47	56	52	49	46	55	51	48	46	45
			1.25	62	57	54	51	61	57	54	51	59	56	53	51	58	55	52	50	49	
下方投影面積		cm ²	1.5	64	60	57	54	63	59	56	54	62	58	56	54	60	57	55	53	52	
			2.0	67	64	61	59	66	63	60	58	64	62	60	58	63	61	59	57	56	
等価発光面積		cm ²	2.5	69	66	63	61	68	65	63	61	66	64	62	60	64	63	61	60	58	
			3.0	70	67	65	63	69	67	65	63	67	65	64	62	66	64	63	61	60	
H _m	1.09H _m	1.09H _m	4.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62	
			5.0	72	70	69	68	71	70	68	67	69	68	67	66	68	67	66	65	63	
			7.0	73	72	71	70	72	71	70	69	70	70	69	68	69	68	67	67	65	
			10.0	74	73	72	71	73	72	71	71	71	71	70	69	70	69	69	68	66	

