

屋内照明器具特性	
品番 (品名)	LGB11039
光源	LED2700_70_518 x1 518.0 lm
管理番号	K0142768(0)DB1
BZ分類	BZ3/0.7/BZ4/2.3/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	11%	床	10%				10%				10%				10%				0%	
下方光束	89%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	60	49	42	38	59	49	42	37	55	47	41	37	53	45	40	36	33
	中	0.63	0.8	69	58	51	46	67	57	50	45	63	55	49	44	59	52	47	43	40
	否	0.56	1.0	74	64	57	52	72	63	56	51	68	60	54	50	64	58	53	49	45
			1.25	79	70	63	58	77	69	62	57	73	66	60	56	69	63	58	54	51
下方投影面積			1.5	83	74	68	63	80	73	67	62	76	69	64	60	72	66	62	58	55
			2.0	88	81	75	70	85	79	73	69	81	75	71	67	76	72	68	65	60
取付高さ	器具間隔最大限		2.5	91	85	79	75	88	83	78	74	84	79	75	71	79	75	72	69	64
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	91	86	81	77	86	82	78	75	81	78	75	72	67
Hm	1.23Hm	1.23Hm	4.0	96	91	88	84	93	89	86	82	89	85	82	79	84	81	79	77	72
			5.0	98	94	91	87	95	92	89	86	90	88	85	83	86	84	82	80	74
			7.0	100	97	94	92	97	95	92	90	93	90	88	87	88	86	85	83	78
			10.0	101	99	97	95	99	97	95	93	94	93	91	90	90	89	87	86	81

