

屋内照明器具特性

| | | |
|---------|---------------------|----------|
| 品番 (品名) | LGB11063 | |
| 光源 | LED2700_70_605 x1 | 605.0 lm |
| 管理番号 | K0142127(0)DB1 | |
| BZ分類 | BZ4/0.9/BZ5/8.5/BZ6 | |

| | | | | | | | | | | | | | | | | | | | | |
|----------------|--------------------|--------------------|---------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 | | 7% | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 |
| 下方光束 | 93% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 59 | 48 | 40 | 35 | 57 | 47 | 40 | 35 | 55 | 45 | 39 | 35 | 52 | 44 | 38 | 34 | 32 |
| | 中 | 0.63 | 0.8 | 67 | 56 | 48 | 43 | 65 | 55 | 48 | 43 | 62 | 53 | 47 | 42 | 59 | 51 | 45 | 41 | 39 |
| | 否 | 0.56 | 1.0 | 72 | 62 | 54 | 48 | 70 | 60 | 53 | 48 | 67 | 58 | 52 | 47 | 63 | 56 | 50 | 46 | 43 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 77 | 67 | 60 | 54 | 75 | 66 | 59 | 53 | 71 | 63 | 57 | 52 | 67 | 61 | 55 | 51 | 48 |
| | | | 1.5 | 81 | 71 | 64 | 58 | 79 | 70 | 63 | 58 | 74 | 67 | 61 | 56 | 70 | 64 | 59 | 55 | 52 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 86 | 78 | 71 | 66 | 84 | 76 | 70 | 65 | 79 | 73 | 68 | 63 | 75 | 70 | 66 | 62 | 58 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 89 | 82 | 76 | 71 | 87 | 80 | 75 | 70 | 83 | 77 | 72 | 68 | 79 | 74 | 70 | 66 | 62 |
| H _m | 1.24H _m | 1.27H _m | 3.0 | 92 | 85 | 80 | 75 | 89 | 84 | 79 | 74 | 85 | 80 | 76 | 72 | 81 | 77 | 73 | 70 | 66 |
| | | | 4.0 | 95 | 90 | 85 | 81 | 93 | 88 | 84 | 80 | 88 | 84 | 81 | 78 | 84 | 81 | 78 | 75 | 71 |
| | | | 5.0 | 97 | 93 | 89 | 85 | 95 | 91 | 87 | 84 | 91 | 87 | 84 | 81 | 87 | 84 | 81 | 79 | 74 |
| | | | 7.0 | 100 | 96 | 93 | 90 | 97 | 94 | 91 | 89 | 93 | 91 | 88 | 86 | 89 | 87 | 85 | 83 | 79 |
| | | | 10.0 | 101 | 99 | 96 | 94 | 99 | 97 | 95 | 93 | 95 | 93 | 91 | 90 | 92 | 90 | 88 | 87 | 82 |

