

屋内照明器具特性

| | | | | | | | | | | |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB11607 | | | | | | | | | |
| 光源 | LED6200_70_3000 x1 3000.0 lm | | | | | | | | | |
| 管理番号 | K0141538(0)DB1 | | | | | | | | | |
| BZ分類 | BZ5/0.7/BZ4/8.5/BZ5 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-------------------|-----------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率 | 97 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| | | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 上方光束 | 6 % | | | | | | | | | | | | | | | | | | | |
| 下方光束 | 91 % | | | | | | | | | | | | | | | | | | | |
| 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 | 0.67 | 0.6 | 5.5 | 4.4 | 3.6 | 3.1 | 5.4 | 4.3 | 3.6 | 3.1 | 5.1 | 4.2 | 3.5 | 3.1 | 4.8 | 4.0 | 3.4 | 3.0 | 2.8 |
| | | 0.63 | 0.8 | 6.5 | 5.5 | 4.7 | 4.2 | 6.4 | 5.4 | 4.7 | 4.2 | 6.0 | 5.2 | 4.6 | 4.1 | 5.7 | 5.0 | 4.5 | 4.0 | 3.8 |
| | | 0.56 | 1.0 | 7.2 | 6.2 | 5.5 | 5.0 | 7.0 | 6.1 | 5.4 | 4.9 | 6.7 | 5.9 | 5.3 | 4.8 | 6.3 | 5.7 | 5.2 | 4.7 | 4.5 |
| | | | 1.25 | 7.8 | 6.9 | 6.2 | 5.7 | 7.6 | 6.8 | 6.1 | 5.6 | 7.2 | 6.5 | 6.0 | 5.5 | 6.9 | 6.3 | 5.8 | 5.4 | 5.1 |
| 下方投影面積 | | cm ² | | | | | | | | | | | | | | | | | | |
| 等価発光面積 | | cm ² | | | | | | | | | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | | | | | | | | | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | | 3.0 | | | | | | | | | | | | | | | | |
| 1.5m | 1.94 m | 1.94 m | 4.0 | | | | | | | | | | | | | | | | | |
| 2 | 2.56 | 2.56 | 5.0 | | | | | | | | | | | | | | | | | |
| 2.5 | 3.18 | 3.17 | 7.0 | | | | | | | | | | | | | | | | | |
| 3 | 3.81 | 3.81 | 10.0 | | | | | | | | | | | | | | | | | |

