

屋内照明器具特性	
品番 (品名)	LGB50044
光源	LED5000_70_1638 x1 1638.0 lm
管理番号	K0140695(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	2%	床	10%				10%				10%				10%				0%				
下方光束	98%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.2	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8			
	中	0.67	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.2	5.2	4.5	4.0	5.9	5.1	4.5	4.0	3.8			
	否	0.63	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.4	4.8	6.8	5.9	5.3	4.8	6.5	5.7	5.2	4.7	4.5			
			1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.5	7.4	6.6	6.0	5.5	7.0	6.4	5.8	5.4	5.1			
下方投影面積		cm ²	1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.0	6.5	6.0	7.4	6.8	6.3	5.9	5.7			
等価発光面積		cm ²	2.0	8.8	8.1	7.5	7.0	8.7	8.0	7.4	6.9	8.3	7.7	7.2	6.8	8.0	7.5	7.1	6.7	6.4			
取付高さ	器具間隔最大限		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.7	7.3	8.3	7.9	7.5	7.2	6.9			
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.3	8.7	8.3	7.9	8.9	8.5	8.1	7.7	8.6	8.2	7.9	7.6	7.3			
1.5m	1.92m	1.97m	4.0	9.8	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.2	8.9	8.6	8.3	8.9	8.6	8.4	8.1	7.8			
2	2.55	2.53	5.0	9.9	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.1	8.9	8.7	8.5	8.1			
2.5	3.17	3.12	7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.7	9.5	9.3	9.1	9.4	9.2	9.0	8.9	8.5			
3	3.8	3.72	10.0	10.3	10.1	9.9	9.8	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.6	9.5	9.3	9.2	8.9			

