

屋内照明器具特性

品番 (品名)	LGBZ1516				
光源	LED6200_70_3350 x1 3350.0 lm				
管理番号	K0147900(0)DB1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	55	43	36	30	54	42	35	30	51	41	34	29	48	39	33	29	26
	中	0.6	0.8	65	54	46	40	63	53	45	40	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	48	70	60	53	47	66	57	51	46	62	55	50	45	42
			1.25	78	68	61	55	76	67	60	54	71	64	58	53	68	61	56	52	49
下方投影面積	cm ²		1.5	82	73	66	60	80	71	65	60	75	68	63	58	72	66	61	57	53
等価発光面積	cm ²		2.0	87	80	74	69	85	78	73	68	81	75	70	66	77	72	68	64	61
取付高さ	器具間隔最大限		2.5	91	84	79	74	89	83	78	73	84	79	75	71	80	76	73	69	65
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	91	86	81	77	87	82	79	75	83	79	76	73	69
Hm	1.26Hm	1.26Hm	4.0	96	92	88	84	94	90	86	83	90	87	83	81	86	83	81	78	74
			5.0	98	95	91	88	96	93	90	87	92	89	86	84	88	86	84	81	77
			7.0	101	98	95	93	98	96	93	91	94	92	90	88	91	89	87	85	81
			10.0	102	100	98	96	100	98	97	95	96	95	93	92	92	91	90	89	84

