

屋内照明器具特性	
品番 (品名)	XNN2569WY
光源	LED2700_85_2255 ×1 2255.0lm
管理番号	K0176088 (＊)DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		ZCM	
下方光束		100 %																					
保守率		良 中 否	0.81	0.6	72	63	58	54	71	63	58	54	69	62	57	54	68	61	57	54	52		
			0.77	0.8	82	74	69	65	80	73	68	65	79	72	68	65	77	71	67	64	63		
			0.68	1.0	87	81	76	72	86	80	75	72	84	79	75	72	82	78	74	71	70		
				1.25	92	86	82	78	91	85	81	78	88	84	80	77	86	83	79	77	75		
下方投影面積		cm ²	1.5	95	89	85	82	93	89	85	82	91	87	84	81	89	86	83	81	79			
			等価発光面積	cm ²	2.0	98	94	91	88	97	93	90	87	95	92	89	87	93	90	88	86	84	
取付 高さ	器具間隔最大限		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	93	91	89	87			
	横方向 (A)		縦方向 (B)		3.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89	
H _m	1.10 H _m	1.10 H _m	4.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	92			
			5.0	104	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	93			
			7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95			
			10.0	106	105	104	104	105	104	103	103	103	102	102	101	101	100	100	99	96			

