

屋内照明器具特性	
品番 (品名)	NTS32240S+NTS92201
光源	LED5000_70_1425 ×1 1425.0 lm
管理番号	K0161315 (0) DB 1
BZ分類	BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		1 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		99 %																								
保守率		良 中 否	0.67	0.6	59	47	40	34	57	46	39	34	55	45	39	34	53	44	38	34	32					
			0.63	0.8	69	59	51	46	68	58	51	46	65	57	50	46	63	55	50	45	43					
			0.56	1.0	76	66	59	54	75	66	59	54	72	64	58	53	69	62	57	53	51					
				1.25	82	73	67	62	81	72	66	61	78	71	65	61	75	69	64	60	58					
下方投影面積		cm ²	1.5	86	78	72	67	85	77	71	67	82	75	70	66	79	73	69	65	63						
等価発光面積		cm ²	2.0	91	85	79	75	90	84	79	75	87	82	77	74	84	80	76	73	70						
取付 高さ	器具間隔最大限		2.5	95	89	84	80	93	88	83	80	90	86	82	79	87	84	80	78	75						
	横方向 (A)		縦方向 (B)	3.0	97	92	88	84	95	91	87	83	92	88	85	82	90	86	84	81	78					
H m	0.91 H m	1.22 H m	4.0	99	96	92	89	98	94	91	88	95	92	89	87	92	90	88	86	83						
			5.0	101	98	95	92	100	97	94	92	97	94	92	90	94	92	90	88	86						
			7.0	103	101	98	96	102	99	97	95	99	97	95	94	96	95	93	92	89						
			10.0	104	103	101	100	103	102	100	99	100	99	98	97	98	97	96	95	92						

