

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NTS32242S+NTS92201           |
| 光源       | LED3500_70_1370 ×1 1370.0 lm |
| 管理番号     | K0161315 (0) DB1             |
| BZ分類     | BZ4                          |

| 器具効率           |                    | 100 %           | 反射率             | 天井                | 80 % |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|----------------|--------------------|-----------------|-----------------|-------------------|------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|--|
|                |                    |                 |                 | 壁                 | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|                |                    |                 |                 | 床                 | 10 % |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束   |                    | 1 %<br>99 %     | 室指数             | 照明率 ( X0.01 ) ZCM |      |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |  |
| 保守率            |                    | 良<br>中<br>否     | 0.67            | 0.6               | 59   | 47  | 40  | 34  | 57   | 46  | 39 | 34  | 55   | 45 | 39 | 34 | 53   | 44 | 38 | 34 | 32  |  |
|                |                    |                 | 0.63            | 0.8               | 69   | 59  | 51  | 46  | 68   | 58  | 51 | 46  | 65   | 57 | 50 | 46 | 63   | 55 | 50 | 45 | 43  |  |
|                |                    |                 | 0.56            | 1.0               | 76   | 66  | 59  | 54  | 75   | 66  | 59 | 54  | 72   | 64 | 58 | 53 | 69   | 62 | 57 | 53 | 51  |  |
|                |                    |                 | 1.25            | 82                | 73   | 67  | 62  | 81  | 72   | 66  | 61 | 78  | 71   | 65 | 61 | 75 | 69   | 64 | 60 | 58 |     |  |
| 下方投影面積         |                    | cm <sup>2</sup> | 1.5             | 86                | 78   | 72  | 67  | 85  | 77   | 71  | 67 | 82  | 75   | 70 | 66 | 79 | 73   | 69 | 65 | 63 |     |  |
| 等価発光面積         |                    |                 | cm <sup>2</sup> | 2.0               | 91   | 85  | 79  | 75  | 90   | 84  | 79 | 75  | 87   | 82 | 77 | 74 | 84   | 80 | 76 | 73 | 70  |  |
|                |                    |                 |                 | 2.5               | 95   | 89  | 84  | 80  | 93   | 88  | 83 | 80  | 90   | 86 | 82 | 79 | 87   | 84 | 80 | 78 | 75  |  |
| 取付高さ           | 器具間隔最大限            |                 | 3.0             | 97                | 92   | 88  | 84  | 95  | 91   | 87  | 83 | 92  | 88   | 85 | 82 | 90 | 86   | 84 | 81 | 78 |     |  |
| H <sub>m</sub> | 0.91H <sub>m</sub> | 縦方向 ( B )       | 4.0             | 99                | 96   | 92  | 89  | 98  | 94   | 91  | 88 | 95  | 92   | 89 | 87 | 92 | 90   | 88 | 86 | 83 |     |  |
|                |                    |                 | 5.0             | 101               | 98   | 95  | 92  | 100 | 97   | 94  | 92 | 97  | 94   | 92 | 90 | 94 | 92   | 90 | 88 | 86 |     |  |
|                |                    |                 | 7.0             | 103               | 101  | 98  | 96  | 102 | 99   | 97  | 95 | 99  | 97   | 95 | 94 | 96 | 95   | 93 | 92 | 89 |     |  |
|                |                    |                 | 10.0            | 104               | 103  | 101 | 100 | 103 | 102  | 100 | 99 | 100 | 99   | 98 | 97 | 98 | 97   | 96 | 95 | 92 |     |  |

