

屋内照明器具特性	
品番 (品名)	L G C 6 2 1 2 0
光源	LED6200_70_6099 ×1 6099.0 lm
管理番号	K0193364 (0) D 1
B Z 分類	B Z 5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	55	43	35	29	53	42	34	29	51	40	34	29	48	39	33	28	26	
			0.6	0.8	65	53	45	39	63	52	45	39	60	50	44	38	57	48	42	38	35	
			0.56	1.0	72	61	53	47	70	59	52	46	66	57	51	45	62	55	49	45	42	
				1.25	77	67	60	54	75	66	59	54	71	64	57	53	68	61	56	52	48	
下方投影面積		cm ²		1.5	82	72	65	60	79	71	64	59	75	68	63	58	72	66	61	57	53	
			等価発光面積	cm ²	2.0	87	79	73	68	85	78	72	67	81	75	70	66	77	72	68	64	61
取付高さ	器具間隔最大限			2.5	91	84	78	74	89	82	77	73	85	79	75	71	81	76	73	69	66	
	横方向 (A)		縦方向 (B)	3.0	93	87	82	78	91	86	81	77	87	83	79	75	83	80	76	73	69	
H m	1.30 H m	1.30 H m	4.0	96	92	88	84	94	90	86	83	90	87	84	81	87	84	81	78	74		
			5.0	98	94	91	88	96	93	89	86	92	89	87	84	89	86	84	82	78		
			7.0	101	98	95	92	99	96	93	91	95	93	90	88	91	89	88	86	82		
			10.0	103	100	98	96	101	99	97	95	97	95	94	92	93	92	91	89	85		

