

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X4 2 0 A E D              |
| 光源       | LED6500_85_2440 ×1 2440.0 lm |
| 管理番号     | K0192144 ( 0 ) D 1           |
| B Z 分類   | B Z 5                        |

| 器具効率     |           | 100 %           | 反射率    | 天井              | 80 % |      |                  |     | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|----------|-----------|-----------------|--------|-----------------|------|------|------------------|-----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|          |           |                 |        | 壁               | 70   | 50   | 30               | 10  | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|          |           |                 |        |                 | 床    | 10 % |                  |     |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|          |           |                 |        |                 |      | 室指数  | 照明率 ( X0.01) ZCM |     |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率      |           | 良<br>中<br>否     | 0.83   | 0.6             | 56   | 43   | 35               | 30  | 54   | 42   | 35 | 30 | 51   | 41   | 34 | 29 | 49   | 40   | 34 | 29 | 27  |     |
|          |           |                 | 0.81   | 0.8             | 65   | 54   | 46               | 40  | 64   | 53   | 45 | 39 | 60   | 51   | 44 | 39 | 57   | 49   | 43 | 38 | 36  |     |
|          |           |                 | 0.77   | 1.0             | 72   | 61   | 53               | 47  | 70   | 60   | 52 | 47 | 66   | 58   | 51 | 46 | 63   | 56   | 50 | 45 | 42  |     |
|          |           |                 |        | 1.25            | 78   | 68   | 60               | 54  | 76   | 66   | 59 | 54 | 72   | 64   | 58 | 53 | 69   | 62   | 56 | 52 | 49  |     |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5             | 82   | 72   | 65               | 60  | 80   | 71   | 64 | 59 | 76   | 69   | 63 | 58 | 72   | 66   | 61 | 57 | 54  |     |
|          |           |                 | 等価発光面積 | cm <sup>2</sup> | 2.0  | 87   | 79               | 73  | 68   | 85   | 78 | 72 | 67   | 81   | 75 | 70 | 66   | 78   | 73 | 68 | 65  | 61  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 91              | 84   | 78   | 73               | 89  | 83   | 77   | 73 | 85 | 80   | 75   | 71 | 81 | 77   | 73   | 70 | 66 |     |     |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 93              | 87   | 82   | 78               | 91  | 86   | 81   | 77 | 87 | 83   | 79   | 75 | 84 | 80   | 77   | 74 | 70 |     |     |
| 1.5m     | 1.96 m    | 2.11 m          | 4.0    | 96              | 92   | 87   | 84               | 95  | 90   | 86   | 83 | 91 | 87   | 84   | 81 | 87 | 84   | 81   | 79 | 75 |     |     |
| 2        | 2.58      | 2.64            | 5.0    | 98              | 94   | 91   | 87               | 97  | 93   | 89   | 86 | 93 | 90   | 87   | 84 | 89 | 87   | 84   | 82 | 78 |     |     |
| 2.5      | 3.21      | 3.2             | 7.0    | 101             | 98   | 95   | 92               | 99  | 96   | 93   | 91 | 95 | 93   | 91   | 89 | 92 | 90   | 88   | 86 | 83 |     |     |
| 3        | 3.84      | 3.77            | 10.0   | 103             | 100  | 98   | 96               | 101 | 99   | 97   | 95 | 97 | 96   | 94   | 92 | 94 | 93   | 91   | 90 | 86 |     |     |

